

Tri-Pro Series

2250WOG

WCB

Metal Seat

FULL PORT

BUTT WELD

HPF43-CS-1-MGG-L-032-B1/B3-C5/C6

FIRE SAFE API 607-7

SIZE 1-1/4"

Actuator ISO Mounting Flange (F05)

NO	Name	Material
1	Body	ASTM A216 WCB
2	Cap	ASTM A216 WCB
3	Ball	Forged SS316 Carbide Coated
4	Seat	Forged SS316 Carbide Coated
5	Gasket (Inner)	Graphite
6	Gasket (Outer)	Graphite
7	Bolt	EN3506 A2-70/A193 B8
8	Stem	17-4PH
9	Seat Gasket	Graphoil
10	Thrust Washer	NIT60
11	Stem Packing	Graphite
12	Packing Follower	SS304
13	Belleville Washer	SS301
14	Tap Lock Washer	SS304
15	Stem Nut	SS304
16	Handle	SS304
17	Stopper	SS304
18	Plastic Cover	Plastic
19	Locking Device	SS304
20	Anti-Static Spring	SS301
21	Anti-Static Ball	SS316
22	Wavo Spring	17-7/Inconel/A286

PRESSURE RATING 2250 WOG

ANSI / FCI LEAKGE CLASS	SHUT-OFF CLASS V/VI
SHELL TEST @ 2250 PSI	ASME B16.34
PRESSURE TEMPERATURE RATING	ASME B16.34
END CONNECTION	ASME B16.11
JOINT STRENGTH	ASME B16.34
WALL THICKNESS	ASME B16.34
BASIC DESIGN	ASME B16.34

Drawn by : M

Checked by : M

Approved by : M

Date : November 9, 2018

Date : November 9, 2018

Date : November 9, 2018

Scale : Not To Scale

Unit : Inch

Material : See Notes

Rev : 0

Sheet : xxx

Drawing Title:

DT-HPF43-CS-1-MGG-L-032-B1/B3-C5/C6

BW 1-1/4"FULL BORE BALL VALVE

4815 W. 5th Street

Lumberton, NC 28358

Website: www.flotite.com

Tel : 910-738-8904

Fax : 910-738-9112

E-mail : flotite@flotite.com